

FVXM-B / RXM-A *perfera*



Perfera Floor Mount

Designed to fit your home effortlessly, delivering comfort without compromise

The Daikin Perfera Floor is a premium floor-standing heat pump that delivers fast, even heating and cooling while also purifying the air for a healthier home. Its unique floor-level airflow and Heat Boost quickly warm the room, keeping feet warm and temperatures balanced throughout the space, while ultra-quiet, energy-efficient operation ensures comfortable, low-cost year-round performance.

Gentle, cosy warmth, utilising Heat+ by Perfera Floor. Create a comfortable radiant heating effect. Make your space feel like it has a fireplace, with all the efficiencies and clean air of a Perfera Floor.

Quiet comfort, day or night with sound levels as low as 19 dB(A), this unit runs quieter than a whisper - perfect for peaceful sleep, focused work, or relaxing family time.

Compact and slim fits neatly under windows, on low walls, or in spaces where traditional heating or wall units won't fit. Its wide system compatibility makes it a flexible choice for both renovations and new builds, adapting easily to different room layouts.

Breathe cleaner, healthier air, combining Daikin's Flash Streamer technology and Silver Allergen filter helps neutralise allergens, odours, and pollutants - ideal for families, allergy sufferers, and anyone who values fresh, clean air.

Smart, effortless control with Daikin's Onecta app, managing your indoor climate is as easy as picking up your phone. Whether you're at home, at work, or away, you can adjust the temperature, change settings, or check energy usage anytime, from anywhere. For hands-free convenience, connect to Google Home or Amazon Alexa and control your comfort with simple voice commands.



ARC466A66



FVXM-B



BRC073 (optional)



RXM25-35A9



WI-FI CONTROL VIA APP



WI-FI ADAPTOR INCLUDED AS STANDARD





FVXM-B / RXM-A *perfera*

R-32 BLUEEVOLUTION

Indoor Units			CVXM20B	FVXM25B	FVXM35B	FVXM50B
Capacity	UK Total Cooling	kW	Multi Combinations Only	2.35	3.32	4.86
	UK Sensible Cooling	kW		1.71	2.22	3.55
	Nominal Cooling	kW		2.4	3.4	5.0
	Nominal Heating	kW		3.4	4.5	5.8
Seasonal Efficiency (EN14825) COOLING	Energy Label			A+++	A++	A++
	Pdesign	kW		2.4	3.4	5.0
	SEER			8.55	8.11	7.20
	Annual Energy Consumption	kWh		98	147	243
Seasonal Efficiency (EN14825) HEATING	Energy Label			A++	A++	A+
	Pdesign	kW		2.3	2.8	4.1
	SCOP		4.65	4.63	4.30	
	Annual Energy Consumption	kWh	692	847	1346	
Air Flow Rate (Cooling)	High / Med / Low / Silent	m ³ /min	8.7 / 7.0 / 4.9 / 4.1	8.7 / 7.0 / 4.9 / 4.1	9.2 / 7.0 / 4.9 / 4.1	11.6 / 9.0 / 6.6 / 5.4
Dimensions	Height	mm	600	600	600	600
	Width	mm	750	750	750	750
	Depth	mm	238	238	238	238
Weight		kg	17	17	17	17
Sound Pressure (Cooling)	High / Med / Low / Silent	dBA	38 / 32 / 25 / 22	38 / 32 / 25 / 20	39 / 32 / 25 / 20	44 / 38 / 31 / 27
Sound Pressure (Heating)	High / Med / Low / Silent	dBA	38 / 32 / 25 / 21	38 / 32 / 25 / 19	39 / 32 / 25 / 19	46 / 40 / 35 / 29
Sound Power (Cooling)		dBA	52	52	53	61

Outdoor Units				RXM25A9	RXM35A9	RXM50A8
Dimensions	Height x Width x Depth	mm	Multi Combinations Only	610 x 923 x 367	610 x 923 x 367	610 x 923 x 367
Weight		kg		36	36	40
Electrical Details	Power Supply			1ph	1ph	1ph
	Maximum Input Current (MCA)	A		10.92	10.92	12.69
	Max Fuse Size	A		13	13	13
Interconnection Wiring	Core / Cable size			3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)		1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)
Pipework	Maximum Length	m		20	20	30
	Maximum Vertical Rise	m		15	15	20
	Precharged to	m		10	10	10
	Additional Charge	g/m	20	20	20	
	Holding Charge	kg	0.95	0.95	0.95	
Sound Pressure (Cooling)	Nominal	dBA	47	47	48	
Sound Pressure (Heating)	Nominal	dBA	49	49	49	
Sound Power (Cooling)		dBA	58	58	61	
Operating Range (Cooling)	Min / Max	°CDB	-10 / 50	-10 / 50	-10 / 50	
Operating Range (Heating)	Min / Max	°CWB	-21 / 18	-21 / 18	-21 / 18	
Air Flow Rate (Cooling)	Nominal	m ³ /min	39.1	39.1	58.0	
Meets ETL criteria			●	●	●	

Notes & Features:

- Wired controller, KLIC-DDV3 and RTD-RA options cannot be combined
- Wireless remote controller with 7-day weekly timer
- Night set mode
- Powerful operation
- Dry programme: reduces humidity in the rooms without variations in internal temperature
- Heat boost function to reach set point quicker during start-up
- Heat+ warms up room for 30min via convection at low fan speed
- Floor warming function to provide even heat distribution up to 3.5m distance
- Connectable with all MXM-A8 multis only due to integrated leak sensor
- Can be connected with R-410A Mini VRV using BPMK boxes

Accessories:

Accessory Ref	Description
EKRS21	Wire harness for new S21 port for all marked (*) options
BRC073*	Wired remote Control - Connection cable required
BRCW901A03	3m extension cord required for wired remote control BRC073
BRCW901A08	8m extension cord required for wired remote control BRC073
KRP413A15*	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A25*	Adaptor PCB for interface to Daikin centralised control systems
KLIC-DDV3*	KNX interface for Split type systems

Accessory Ref	Description
RTD-RA*	Adaptor PCB for Modbus connection and/or extended system functions
K.CWB90-2	Wall bracket (90kg, 500mm support arm)
K.DT1	Condensate drip tray for use with Split ODU - tray width 800mm
K.FF6005	Two flexi-feet (Standard 600mm x 185mm x 100mm) to mount the outdoor unit
K.CGS	Condensing unit guard (750 x 1050 x 460)
K.CGM	Condensing unit Guard (1150 x 1150 x 650)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com